


## Light Tower: LT7M4x400J-Y

50 HZ 50 hz

 Cooling System: Air

 Diesel

### Features

|                                  |                    |
|----------------------------------|--------------------|
| Model                            | LT7M4x400J-Y       |
| Frequency                        | 50 Hz              |
| A.C. Output Lamps                | 4x1000 W           |
| Lamp Type                        | Alogen             |
| A.C. Output Generator (max-cont) | 5kW - 4,4kW        |
| Lifting                          | with manual winch  |
| Fuel Tank Capacity (l)           | 100.00             |
| Dimensions (mm)                  | 2626 x 1353 x 2500 |
| Dimensions in Function (mm)      | 2626 x 2400 x 7000 |
| Weight (Kg)                      | 590                |
| Sound Power Level * (LwA)        | 95                 |
| Acoustic Pressure (LpA) **       | 70                 |

### Engine

|                               |        |
|-------------------------------|--------|
| Model                         | L100N  |
| Brand                         | YANMAR |
| Rpm                           | 3000   |
| Fuel                          | Diesel |
| Fuel Consumption at 75% (1/4) | 1.40   |

### Standards Applied

- Control panel with voltmeter and hourmeter
- Auto engine protection shutdown system in case of low oil pressure and high temperature engine
- 12V built-in battery with electric start
- Fuel level gauge

- Emergency stop push-button
- 1x16 A 230 V single-phase socket protected by circuit breaker
- 3 stabilizers
- 2 wheels site tow undercarriage



Foto Indicativa - Indicative Picture

### Other Features

- Insulation class H
- Ambient temperature
- Altitude 1000 mt
- IP 23

### Accessories Upon Request

- Floodlight with metal halide lamps
- Floodlight with LED lamps
- Hydraulic lifting
- 2 wheels road tow
- Low temperature kit
- Dusk sensor
- 4 stabilizers
- ATEX Homologation
- Homologation "Directive 2000/14/EC"

fr